



DISTRIBUTED BY CLEARLAKE SUPPLY

847.686.2890

FEATURES

- Vulcanized Recycled Rubber
- Suitable for most Rooftop Material
- UV Resistant
- Noise/Vibration Dampening
- Highly Resistant to Freeze/Thaw
- Reflector for High Visibility
- Indented hand hold design/easy transport

APPLICATIONS

- Solar Racking
- HVAC Ducting
- HVAC System Support
- Pipe/Conduit Support
- Cable Tray Systems
- Roof Walkway Systems

INDEPENDENT LAB TESTING

- Ozone Exposure ASTM D1149-18
- Heat Aging ASTM D573-2019
- Hardness (Durometer Shore A) ASTM D2240-2021
- Compressive Strength ASTM D395-2018
- Tensile Testing ASTM D412-2016

FINISHES

- Pre-Galvanized Steel Strut
- Other special order finishes available

MODEL	STRUT LENGTH	STRUT HEIGHT	BLOCK LENGTH	BLOCK HEIGHT	WIDTH	ADJ. ROD HEIGHT	LOAD CAPACITY*	WEIGHT
<input type="checkbox"/> T210VA-1-8	10 1/2"	13/16"	10 1/2"	5"	5"	8"	400 LBS	5.38 LBS
<input type="checkbox"/> T210VA-1-12	10 1/2"	13/16"	10 1/2"	5"	5"	12"	400 LBS	5.69 LBS
<input type="checkbox"/> T210VA-1-16	10 1/2"	13/16"	10 1/2"	5"	5"	16"	400 LBS	6.56 LBS



*Uniform block load capacity only. Always consult engineer for substrate load capacity.



www.talonroofingproducts.com



info@talonroofingproducts.com

